



Engine Drive Selection

		EnPak® A28GBW	EnPak® A60GE	EnPak® A60HGE	Bobcat™ 200 Air Pak™	Trailblazer® 302 Air Pak™	Big Blue® 600 Air Pak™	Big Blue® 800 Duo Air Pak™
Air		28 cfm, 175 psi	60 cfm, 120 – 175 psi	60 cfm, 120 – 175 psi	28 cfm, 175 psi	31 cfm, 160 psi	60 cfm, 100 psi	60 cfm, 100 psi
Battery Charger 12/24 V Crank Assist		●	Aftermarket options available	Aftermarket options available	●	●		
Load-Management			●	●				
Auto Start/Stop Technology			●	●				
EnVerter™ Technology			●	●				
Hydraulics				20 gpm hydraulic pump				
Aux Power (watts)		5,500	6,000	6,000	5,500	11,000	12,000	12,000
Weld Output Range (A)		45 – 210	1 – 200 With Maxstar or Multimatic added	1 – 200 with Maxstar added	50 – 210	10 – 350	20 – 600	Single Weld Mode: 40 – 800 Dual Weld Mode: 20 – 400"
Industries	Agriculture	✓	✓	✓	✓	✓		
	Construction	✓	✓	✓	✓	✓	✓	✓
	Mining	✓	✓	✓	✓	✓	✓	✓
	Municipal	✓	✓	✓	✓	✓	✓	✓
	Propane	✓	✓	✓	✓		✓	✓
	Railroad	✓	✓	✓	✓	✓	✓	✓
	Utility	✓	✓	✓	✓	✓	✓	✓
	Logging	✓	✓	✓	✓	✓		
Truck Class		3 – 5	5 – 7	5 – 7	3 – 5	3 – 5	5 – 7	5 – 7
Controls		Remote panel	Remote panel	Remote panel			Optional lower controls	Optional lower controls
Dimensions of Remote Panel	Width	4.06 in	1.8 in	1.8 in .0				
	Height	15.97 in	5.25 in	5.25 in				
	Length	16.49 in	7.13 in	7.13 in				
Weight (Not including remote panel)		558 lbs	786 lbs	832 lbs	558 lbs	771 lbs	2040 lbs	2095 lbs
Dimensions	Width	20.25 in (51.4 cm)	21 in (53.5 cm)	21 in (53.5 cm)	23.76 in (60.4 cm)	20 in (50.8 cm)	28.5 in (72.7 cm)	28.5 in (72.7 cm)
	Height	24.25 in (61.6 cm)	30 in (76.2 cm)	30 in (76.2 cm)	29.78 in (75.6 cm)	34.5 in (87.6 cm)	46 in (116.8 cm)	46 in (116.8 cm)
	Length	46 in (116.8 cm)	47 in (119.4 cm)	47 in (119.4 cm)	20 in (50.8 cm)	59.6 in (151.5 cm)	69.5 in (176.5 cm)	69.5 in (176.5 cm)
Fuel Type		Gasoline	Diesel	Diesel	Gasoline	Gasoline	Diesel	Diesel