



Engine Drive Selection

		EnPak® A30GBW	EnPak® A60GE	EnPak® A60HGE	Bobcat™ 200 Air Pak™	Trailblazer® 302 Air Pak™	Big Blue® 600 Air Pak™	Big Blue® 800 Duo Air Pak™
Air		30 cfm, 175 psi	60 cfm, 120 – 175 psi	60 cfm, 120 – 175 psi	30 cfm, 175 psi	31 cfm, 160 psi	60 cfm, 100 psi	60 cfm, 100 psi
Battery Charger 12/24 V Crank Assist		●	Aftermarket options available	Aftermarket options available	●	●		
Load-Management		Auto-Speed™	●	●	Auto-Speed™			
Auto Start/Stop Technology		●	●	●				
EnVerter™ Technology			●	●				
Hydraulics				20 gpm hydraulic pump				
Aux Power (watts)		6,500	6,000	6,000	6,500	11,000	12,000	12,000
Weld Output Range (A)		30 – 210	1 – 200 With Maxstar or Multimatic added	1 – 200 with Maxstar added	30 – 210	10 – 350	20 – 600	Single Weld Mode: 40–800 Dual Weld Mode: 20 – 400
Industries	Agriculture	✓	✓	✓	✓	✓		
	Construction	✓	✓	✓	✓	✓	✓	✓
	Mining	✓	✓	✓	✓	✓	✓	✓
	Municipal	✓	✓	✓	✓	✓	✓	✓
	Propane	✓	✓	✓	✓	✓	✓	✓
	Railroad	✓	✓	✓	✓	✓	✓	✓
	Utility	✓	✓	✓	✓	✓	✓	✓
	Logging	✓	✓	✓	✓	✓		
Truck Class		3 – 5	5 – 7	5 – 7	3 – 5	3 – 7	5 – 7	5 – 7
Controls		Main Control panel & Weld/Battery Output panel (optional 120/240V Outlet panel)		Remote panel	Remote panel		Optional lower controls	Optional lower controls
Dimensions of Remote Panel		Main Control panel	Weld/Battery Output panel					
	Width	3.19 in	3.90 in	1.8 in	1.8 in			
	Height	5.48 in	5.43 in	5.25 in	5.25 in			
	Length	16.24 in	9.62 in	7.13 in	7.13 in			
Weight (Not including remote panel/s)		Gas: 524 lbs Diesel: 568 lbs		786 lbs	832 lbs	Gas: 514 lbs Diesel: 618 lbs	771 lbs	2040 lbs
Dimensions	Width	20 in (50.8 cm)		21 in (53.5 cm)	21 in (53.5 cm)	20 in (50.8 cm)	20 in (50.8 cm)	28.5 in (72.7 cm)
	Height	28 in (71.1 cm)		30 in (76.2 cm)	30 in (76.2 cm)	29 in (73.4 cm)	34.5 in (87.6 cm)	46 in (116.8 cm)
	Length	47 in (119.2 cm)		47 in (119.4 cm)	47 in (119.4 cm)	47 in (119.2 cm)	59.6 in (151.5 cm)	69.5 in (176.5 cm)
Fuel Type		Gas* or Diesel		Diesel	Diesel	Gas* or Diesel	Gas	Diesel

*Gas models of the EnPak A30 and Bobcat 200 Air Pak will be available April 2019.