

Face Shield Series

Industrial-Strength Shields

Quick Specs

Typical Applications

Chipping
Wire brushing
Grinding
Oxy-fuel cutting
Brazing
Soldering

Lens Dimensions

Height x Width x Thickness
8.4 x 8.6 x 0.8 in. (213 x 218 x 2.1 mm)

Shades

Clear
Clear Anti-Fog
Shade 3
Shade 5

Assigned Protection Factor (APF) 10

Certifications

- ANSI Z87.1
- CSA Z94.3

Weight 4.4 oz. (123.8 g)



NEW!

HDV technology for a sharp detailed view at any angle without distortion.

Durable protection. Impact-resistant shield for increased durability and protection.

Lightweight design for all-day wear and comfort.

Anti-Fog coating prevents fogging for enhanced visibility.

Shade 3 and 5 lenses provide protection for cutting, brazing or soldering applications.

Made of polycarbonate material that provides 99.9 percent UVA/UVB/UVC protection to help prevent eye damage.



Warrantied for 90 days.



Miller Electric Mfg. LLC

An ITW Welding Company
1635 West Spencer Street
P.O. Box 1079
Appleton, WI 54912-1079 USA

Equipment Sales US and Canada

Phone: 866-931-9730
FAX: 800-637-2315
International Phone: 920-735-4554
International FAX: 920-735-4125

MillerWelds.com



Lens Options



Clear
288269



Clear
Anti-Fog
288274



Shade 3
288270



Shade 5
288273

Replacement Parts/Accessories



Replacement
Clear Lens
288275



Replacement
Clear Anti-Fog Lens
288278



Replacement
Shade 3 Lens
288276



Replacement
Shade 5 Lens
288277



Replacement
Headgear and Crown
288280



Halo Hard Hat Adapter
222003
Slotted Hard Hat Adapter Clips
(Not Shown) 259637

Ordering Information

Protective Face Shields	Stock No.	Description	Qty.	Price
Face Shield Series	288269	Clear		
	288274	Clear Anti-Fog		
	288270	Shade 3		
	288273	Shade 5		
Replacement Parts/Accessories				
Replacement Lens	288275	Clear		
	288278	Clear Anti-Fog		
	288276	Shade 3		
	288277	Shade 5		
Replacement Headgear and Crown	288280	Compatible with ALL lens options		
Halo Hard Hat Adapter	222003			
Slotted Hard Hat Adapter Clips	259637			

Date:

Total Quoted Price:

Distributed by:

