





















# Small Frame Millermatic® and Multimatic® Comparison

						
<b>PROCESS CAPABILITIES</b>		<b>Millermatic 141</b>	<b>Millermatic 211</b>	<b>Multimatic 200</b>	<b>Multimatic 215</b>	<b>Multimatic 220 AC/DC</b>
	MIG/flux-cored	■	■	■	■	■
	DC stick			■	■	■
	DC TIG			■	■	■
	AC TIG					■
	DC pulsed TIG					■
<b>WELDING CAPABILITY</b>						
Mild and stainless steel	Min	24 ga.	24 ga.	24 ga.	24 ga.	24 ga.
	Max	3/16 in.	3/8 in.	3/8 in.	3/8 in.	3/8 in.
Aluminum	Min	18 ga.	18 ga.	18 ga.	18 ga.	24 ga.
	Max	14 ga.	3/8 in.	3/8 in.	3/8 in.	3/8 in.
<b>POWER</b>						
Input power	V	120	120/240	120/240	120/240	120/240
Amperage range	A	30-140	30-230	5-200	20-230	20-230
<b>FEATURES</b>						
Auto-Set™		■	■	■	■	■
MVP™			■	■	■	■
Color LCD display					■	■
QuickTech™						■
Pro-Set™						■
TIG high-frequency starts						■
<b>PRICING</b>		\$	\$	\$\$	\$\$	\$\$\$

▼ See next page for Large Frame Millermatic® and Multimatic® Comparison ▼

# Large Frame Millermatic® and Multimatic® Comparison

						
<b>PROCESS CAPABILITIES</b>		<b>Millermatic 212 Auto-Set</b>	<b>Millermatic 252</b>	<b>Millermatic 255</b>	<b>Multimatic 255</b>	<b>Millermatic 350P</b>
	MIG/flux-cored	■	■	■	■	■
	Pulsed MIG			■	■	■
	DC stick   including 6010				■	
	DC TIG				■	
	DC pulsed TIG				■	
<b>WELDING CAPABILITY</b>						
Mild and stainless steel	Min	22 ga.	22 ga.	24 ga.	24 ga.	24 ga.
	Max	3/8 in.	1/2 in.	1/2 in.	1/2 in.	1/2 in.
Aluminum	Min	14 ga.	14 ga.	18 ga.	18 ga.	18 ga.
	Max	3/8 in.	3/8 in.	1/2 in.	1/2 in.	1/2 in.
<b>POWER</b>						
Input power	V	208/230	208/230 or 230/460/575	208/240	208-575	208/230/460 1- and 3-phase
Amperage range	A	30-210	30-300	20-350	5-350	25-400
<b>FEATURES</b>						
12-inch wire spool		■	■	■	■	■
Auto-Set™		■		■	■	
Program memory settings				■	■	
Auto-Line™				■	■	
Easy to read and use 7-inch color LCD display				■	■	
Detachable cart				■	■	
<b>PRICING</b>		\$\$	\$\$\$	\$\$\$	\$\$\$	\$\$\$\$