

# N95

## Disposable Mask Respirator

### Quick Specs

**Filter Type**

**N95 Filter Media**

Provides 95% filtration of airborne particles


- Stainless steel (hexavalent chromium), galvanized steel (zinc oxide), steel/manganese alloys, aluminum, cadmium and lead fumes
- Optional N95 nuisance level OV relief respirators are available\*

**Assigned Protection Factor (APF)** 10

**Certifications** NIOSH 42 CFR 84

**Weight** 1.1 oz. (32 g)

**One Size Available**



**N95 filter media captures airborne particles**



**Ideal for use with a welding helmet**

**Flame-retardant outer layer** offers necessary protection for welding applications.

**Ergonomic design** allows user to feel more comfortable and less constricted without compromising the efficiency and effectiveness of the mask.

**Large non-return exhaust valve** reduces heat build-up and user fatigue.

**Fully adjustable double head-straps** allow for a comfortable, secure fit.

**Preformed nose area** with adjustable aluminum nose clip allows for a customized fit.

**Full inside foam seal** enhances fit and improves overall mask seal.

**N95 nuisance level OV relief respirators** (optional) feature an added layer of carbon that helps remove nuisance level organic vapor odors\*

*\*N95 nuisance level OV relief respirators are designed for use with organic vapor concentrations not exceeding OSHA's PELs or other applicable government occupational exposure limits, whichever is lower.*



**Miller Electric Mfg. Co.**  
An ITW Welding Company  
1635 West Spencer Street  
P.O. Box 1079  
Appleton, WI 54912-1079 USA

**Equipment Sales US and Canada**  
Phone: 866-931-9730  
FAX: 800-637-2315  
International Phone: 920-735-4554  
International FAX: 920-735-4125

**MillerWelds.com**  
   



## Ordering Information

Respirator	Stock No.	Description	Qty.	Price
N95 Disposable Respirator	#267 334	Respirator with valve, 10 pack		
	#267 335	Respirator with valve and nuisance level OV relief, 10 pack		

Date: Total Quoted Price:

---

Distributed by:

